

PRODUCT SPECIFICATIONS



Washrite Model T3000A

RACK CONVEYOR DISHWASHER
INTEGRAL TYPE 'A' AIR BREAK & BOOSTER PUMP



► Specially designed stainless steel, indented anti-clog wash and rinse arms, easily removed for cleaning, without tools ► Pressed moulded wash tank with radiused corners and double filters for hygiene & easy maintenance ► High efficiency, self draining wash pumps for greater hygiene & ultimate washing power ► Double skinned insulated cabinet construction reduces energy costs, noise levels and keeps the wash area ambient temperature to an absolute minimum ► Insulated rinse boiler ► Panoramic counter-balanced inspection doors for safe & easy access ► Constructed entirely from AISI 304 grade stainless steel ► 24 Volts control circuit for ultimate safety ► Rinse economy device for saving water and energy

Technical Details

Rack Conveyor Dishwasher T3000A

	Baskets/h	Plates/h
Electromechanical control panel with temperature display		
Wash cycle I	112	2016
Wash cycle II	169	3042
Dimensions (W x D x H)	2150 x 790 x 1680 mm	
Clear entry height	460 mm	
Zones	Prewash / Wash / Rinse	
Prewash pump / wash pump power	1.37kW / 1.37 kW	
Tank element	8.0 kW	
Boiler element	20.0kW	
Total electrical load	31.15 kW	
Electrical supply	400 Volts 3 Phase + Neutral 50 Hz	
Water supply temperature	65°C maximum	
Water supply pressure	1.0 bar minimum*	
Water supply hardness	7°Clark maximum**	
Inlet water connection	¾" BSP	
Drain connection	1½"	
Height of drain connection on dishwasher (for gravity drain)	100mm	
Prewash / wash temperature	40 - 45 / 55 - 60°C	
Rinse temperature	82 - 85°C	
Prewash tank / wash tank capacity	40 / 80 litres	
Boiler capacity	24 litres	
Rinse water consumption	285 litres / hour	
Prewash pump/wash pump circulation capacity	503 / 644 litres / minute	

*If supply pressure less than 1.0 bar, external booster pump required

**If water hardness greater than 7°Clark, external water softener required

Features and accessories

Integral Type 'A' Air Break & Rinse Booster Pump	Standard
Powerful anti-clog wash and rinse arms	Standard
Inlet splash guard 250 mm long	Standard
Door safety micro switch	Standard
Double skinned cabinet	Standard
Rinse economy device	Standard
Insulated rinse boiler	Standard
24 Volts electrical controls	Standard
Automatic start	Standard
Prewash zone 600mm with double deep filter system	Standard
Steam condenser unit	Option
Heat Recovery system with heat pump (+ 600 mm length)	Option
9kW or 12kW drying zone (+ 610 mm length)	Option
Steam extractor unit	Option
Outlet splashguard 250 mm long	Option
14, 18, or 20kW supplementary internal boiler	Option
Dishwasher tables and sinks(s) with spray arm, etc.	Option
Extended warranty	Option
Preventative maintenance contract	Option

Proton Southern Limited, Proton House, West Quay Road, Southampton SO15 1GZ

Telephone: 02380 632766 Fax: 02380 344180

e-mail: generalenquiries@proton-washrite.co.uk

website: www.proton-washrite.co.uk

