

PRODUCT SPECIFICATIONS



Washrite Model W350

GLASSWASHER

► Specially designed stainless steel, indented anti-clog wash arm, easily removed for cleaning, without tools ► With double tank filters for hygiene and easy maintenance, to protect wash pump and drain pump when installed ► 20 cm clear wash height ► Door safety micro switch ► The new wash pump is designed to guarantee electrical savings but also a higher wash performance and reduced noise level (48dBA)

Technical Details

Glasswasher W350

	(sec.)	Baskets/h	Glasses/h (approx)
Electromechanic control panel			
Wash cycle I	120	30	750
Dimensions (W x D x H)		420 x 470 x 585 mm	
Clear entry height		200 mm	
Basket size		350 x 350 mm	
Wash pump power		0,17 kW	
Tank element / boiler element		1,6 kW / 2,6 kW	
Total electrical load / Electrical supply		2,77 kW / 230 Volts 1 Phase 50 Hz	
Water supply temperature		65°C maximum	
Water supply pressure		2 bar minimum*	
Water supply hardness		7° Clark maximum**	
Inlet water connection		¾" BSP	
Drain connection		1¼" minimum, 1½" recommended	
Height of drain connection on glasswasher (for gravity drain)		35mm (drain pump optional)	
Wash temperature		60°C	
Rinse temperature		70 - 85°C (adjustable)	
Wash tank capacity		11 litres	
Boiler capacity		2.7 litres	
Water consumption per cycle		2.4 litres	
Wash pump circulation capacity		109 litres/minute	

*If supply pressure less than 2 bar, external booster pump required

**If water hardness greater than 7°Clark, external water softener required

Features and accessories

Double wash tank filters	Standard
Lower wash arm & upper and lower light weight rinse arms	Standard
Detergent dosing (peristaltic pump)	Standard
Rinse aid dosing (diaphragm injector)	Standard
Water inlet hose, waste hose, main power cable	Standard
Door safety micro switch	Standard
Single skinned cabinet	Standard
Two glasswash baskets & one teaspoon holder	Standard
External rinse booster pump	Option
Drain pump	Option
Machine stand (for optimum working height/gravity drain)	Option
Manual and automatic water softeners	Option
Basket drying rack	Option
Glasswashing station with sink(s) & racking	Option
Special glasswash baskets	Option
Glasswash detergent	Option
Glasswash rinse aid	Option
Extended warranty	Option
Preventative maintenance contract	Option

Proton Southern Limited, Proton House, West Quay Road, Southampton SO15 1GZ

Telephone: 02380 632766 Fax: 02380 344180

e-mail: generalenquiries@proton-washrite.co.uk

website: www.proton-washrite.co.uk

