

# PRODUCT SPECIFICATIONS



## Washrite Model X700A

FRONT LOADING DISHWASHER WITH DOUBLE SKINNED CABINET  
INTEGRAL TYPE 'A' AIR BREAK & BOOSTER PUMP

► Specially designed stainless steel, indented anti-clog wash arms, easily removed for cleaning, without tools ► Pressed moulded basket guides ► Double skinned insulated cabinet construction reduces energy costs, noise levels (62 dBA) and keeps the wash area ambient temperature to an absolute minimum ► 32 cm clear wash height ► Door safety micro switch ► Peristaltic chemical pumps

## Technical Details

### Front Loading Dishwasher X700A

	(sec.)	Baskets/h	Plates/h	Glasses/h (approx)
Electromechanical control panel				
Wash cycle I	120	30	420	1080
Wash cycle II	180	20	360	720
Dimensions (W x D x H)			585 x 610 x 825 mm	
Clear entry height			320 mm	
Basket size			500 x 500 mm	
Wash pump power			0.4 kW	
Tank element			2.0 kW	
Boiler element			2.6 kW (13A) 4.0kW (20A)	
Total electrical load			3.0 kW (13A) 4.4kW (20A)	
Electrical supply			230 Volts 1 Phase 50 Hz	
Water supply temperature			65°C maximum	
Water supply pressure			0.7 bar minimum*	
Water supply hardness			7°Clark maximum**	
Inlet water connection			¾" BSP	
Drain connection			1½"	
Height of drain connection on dishwasher (for gravity drain)			65mm (drain pump optional)	
Wash temperature			60°C	
Rinse temperature			82 - 85°C	
Wash tank capacity			26 litres	
Boiler capacity			5.5 litres	
Water consumption per cycle			2.5 litres	
Wash pump circulation capacity			261 litres/minute	

\*If supply pressure less than 0.7 bar, external booster pump required

\*\*If water hardness greater than 7°Clark, external water softener required

### Features and accessories

Integral Type 'A' Air Break & Rinse Booster Pump	<b>Standard</b>
Powerful anti-clog wash arms and contra rotating lightweight rinse arms	<b>Standard</b>
Detergent dosing (peristaltic pump)	<b>Standard</b>
Rinse aid dosing (peristaltic pump)	<b>Standard</b>
Water inlet hose, waste hose, main power cable	<b>Standard</b>
Door safety micro switch	<b>Standard</b>
Double skinned cabinet	<b>Standard</b>
Three dishwash baskets & one teaspoon holder	<b>Standard</b>
External rinse booster pump	Option
Drain pump	Option
Machine stand (for optimum working height/gravity drain)	Option
Manual and automatic water softeners	Option
Dishwashing station with sink(s), spray arm etc.	Option
Dishwash detergent	Option
Dishwash rinse aid	Option
Extended warranty	Option
Preventative maintenance contract	Option

Proton Southern Limited, Proton House, West Quay Road, Southampton SO15 1GZ

Telephone: 02380 632766 Fax: 02380 344180

e-mail: [generalenquiries@proton-washrite.co.uk](mailto:generalenquiries@proton-washrite.co.uk)

website: [www.proton-washrite.co.uk](http://www.proton-washrite.co.uk)

