

Product Specification

washrite

Washrite Model W1400A DUO

High capacity 60 litre wash tank

- > 3 Phase machine for rapid heating and maximum power
- > 20kw Boiler element
- > Straight Line or Corner Feed Dishwasher
- > 2 x 500mm square baskets / 2160 plates per hour
- > 1,2,3 or 8 minute cycle (operator-selected)
- > Stainless steel wash arms with anti-block jets
- > Internal detergent & rinse aid pumps available as optional extra
- > Internal rinse booster pump
- > Drain pump available as optional extra
- > Double-skinned & insulated stainless steel construction
- > Full-width wash tank top filters
- > Supplied complete with 4 baskets
- > Fits to existing tables (subject to survey)
- > New table options, made to order
- > Suitable applications include large pub/restaurants, hotels, canteens, hot and cold feed installations
- > Dimensions 1181mm(w) x 796mm(d) x 1950mm(h) – hood open
- > 12 months on-site parts & labour warranty



Technical Details

Electromechanical control panel	
Four wash cycles, operator selected	1, 2, 3 and 8 minutes
Dimensions (W x D x H)	1181 x 796 x 1950 mm
Clear entry height	430 mm
Basket size	500 x 500 mm
Wash pump power	2.2 kW
Tank element	7.5 kW
Boiler element	20 kW
Total electrical load	22.2 kW
Electrical supply	400 Volts 3 Phase xx Hz
Water supply temperature	60°C maximum
Water supply pressure	0.7 bar minimum*
Water supply hardness	7° Clark maximum**
Inlet water connection	3/4" BSP
Drain connection	1.5"
Height of drain connection on dishwasher (for gravity drain)	150 mm (drain pump optional)
Wash temperature	60°C
Rinse temperature	85° C
Wash tank capacity	60 litres
Water consumption per cycle	5.2 litres

Features and accessories

Integral Type 'A' Air Break & Rinse Booster Pump	Standard
Powerful anti-clog wash arms and contra rotating lightweight rinse arms	Standard
Detergent dosing (peristaltic pump)	Standard
Rinse aid dosing (peristaltic pump)	Standard
Water inlet hose, waste hose, main power cable	Standard
Door safety micro switch	Standard
Double skinned cabinet	Standard
Three dishwash baskets & one teaspoon holder	Standard
External rinse booster pump	Option
Drain pump	Option
Machine stand (for optimum working height/gravity drain)	Option
Manual and automatic water softeners	Option
Dishwashing station with sink(s), spray arm etc.	Option
Dishwash detergent	Option
Dishwash rinse aid	Option
Extended warranty	Option

*If supply pressure less than 0.7 bar, external booster pump required

**If water hardness greater than 7°Clark, external water softener required

Proton Southern Limited, Proton House, West Quay Road, Southampton SO15 1GZ

T: 02380 632766 F: 02380 344180 E: generalenquiries@proton-washrite.co.uk

www.proton-washrite.co.uk

